



MYSTIQUE 42

LIMITED LIFETIME WARRANTY

**DISTINGUISH YOUR HOME'S
GRACE AND CHARACTER**

*"Graceful character,
powerful protection"*

Mystique 42 shingles, uniquely designed with oversized tabs, feature dramatic 3-dimensional shadow bands to create a sharp, slate look, both eye-catching and strikingly elegant.

Choose from a superb palette of vintage colours designed to instantly enhance your home's curb appeal.

▼
Use BP Accu-Ridge or Yukon SB for Hip & Ridge



With



Product colour shown: Slate Black

VINTAGE SELECTION



AUTUMN BROWN



SUNSET CEDAR



SILVER GREY



SEYCHELLES BLUE



WEATHERED ROCK



BOREAL GREEN



MAGENTA RED



SHADOW BLACK

Due to limitations of the printing process, actual shingle colours and granule blends could be different from the photos.



EARTH TONE SELECTION



ANTIQUE WOOD



BROWN STONE



BEACHWOOD



TWILIGHT GREY



STONE WOOD



SLATE BLACK



CLASS 3 IMPACT RESISTANCE

MYSTIQUE 42 MEETS THE FM 4473 IMPACT RESISTANCE CLASS 3 REQUIREMENTS.

Mystique 42, built with a SeBS elastomeric compound provides proven FM performance.

On top of enhancing the impact resistance of the shingle, the modified asphalt improves the flexibility of the material, yielding better reaction to freeze-thaw cycles and improves the granules retention that protect the asphalt from UV degradation.

Mystique 42 shingles are backed by BP's Limited Lifetime Warranty

It is recommended that you view a full size shingle before making a final colour selection. We reserve the right to change colours at any time.

SPECIFICATIONS

DIMENSIONS (APPROX.)	EXPOSURE	AVERAGE NUMBER OF SHINGLES PER 3 BUNDLE	AVERAGE COVERAGE PER BUNDLE	INSTALLATION	SPEC. COMPLIANCE	WARRANTY PERIOD (YRS)	WIND PROTECTION*
----------------------	----------	---	-----------------------------	--------------	------------------	-----------------------	------------------

THE ARCHITECT COLLECTION • LAMINATE SHINGLES

VANGARD 42 IR

1067 mm x 356 mm (42" x 14")	152 mm (6")	57	3.06 m ² (32.9 sq. ft.)	Standard slope: ≥ 1:3 (4/12) Low slope: ≥ 1:6 (2/12) to < 1:3 (4/12)	CSA A123.5, CSA A123.51 ASTM D3462, ASTM D3018, ASTM D7158 – Class H ASTM E108, ASTM D3161 – Class F UL 790 Fire Resistance A Meets UL 2218 Impact Resistance Class 4 Pass TAS 100 as referenced in Miami-Dade County Meets Class H as tested per UL2390	Lifetime	STANDARD Application ¹ : 180 km/h (110 mph)	HIGH WIND Application ² : 220 km/h (135 mph)
---------------------------------	----------------	----	---------------------------------------	--	---	----------	--	---

MANOIR

1029 mm x 343 mm (40 ½" x 13 ½")	146 mm (5 ¾")	60	3 m ² (32.3 sq. ft.)	Standard slope: ≥ 1:3 (4/12) Low slope: ≥ 1:6 (2/12) to < 1:3 (4/12)	CSA A123.5, CSA A123.51, CSA A123.52 ASTM D3462, ASTM D3018 ASTM D7158 – Class D ASTM E108, ASTM D3161 – Class F UL 790 Fire Resistance A Pass TAS 100 as referenced in Miami-Dade County Meets Class D as tested per UL2390	Lifetime	STANDARD Application ¹ : 180 km/h (110 mph)	HIGH WIND Application ² : 220 km/h (135 mph)
-------------------------------------	------------------	----	------------------------------------	--	--	----------	--	---

MYSTIQUE 42

1067 mm x 356 mm (42" x 14")	152 mm (6")	57	3.06 m ² (32.9 sq. ft.)	Standard slope: ≥ 1:3 (4/12) Low slope: ≥ 1:6 (2/12) to < 1:3 (4/12)	CSA A123.5, CSA A123.51, CSA A123.52 ASTM D3462, ASTM D3018, ASTM D7158 – Class H ASTM E108, ASTM D3161 – Class F Meets FM 4473 Impact Resistance Class 3 UL 790 Fire Resistance A Pass TAS 100 as referenced in Miami-Dade County Meets Class H as tested per UL2390	Lifetime	STANDARD Application ¹ : 180 km/h (110 mph)	HIGH WIND Application ² : 220 km/h (135 mph)
---------------------------------	----------------	----	---------------------------------------	--	---	----------	--	---

THE CLASSIC COLLECTION • 3-TAB SHINGLES

YUKON SB


1000 mm x 336 mm (39 ¾" x 13 ¼")	143 mm (5 ⅝")	21 (per bundle)	3 m ² (32.3 sq. ft.) or 9 linear m (29.6 linear ft.) if used as Hip & Ridge	Standard slope: ≥ 1:3 (4/12) Low slope: ≥ 1:6 (2/12) to < 1:3 (4/12)	CSA A123.5, CSA A123.51, CSA A123.52 ASTM D3462, ASTM D3018, ASTM D7158 – Class D ASTM D3161 – Class F UL 790 Fire Resistance A Pass TAS 100 as referenced in Miami-Dade County Meets Class D as tested per UL2390	30 years	STANDARD Application ¹ : 115 km/h (70 mph)	HIGH WIND Application ² : 130 km/h (80 mph)
-------------------------------------	------------------	--------------------	---	--	--	----------	---	--

1. Standard Wind Warranty applies when shingles are installed using standard application. 2. High Wind Warranty applies when shingles are installed using high wind application.

* Please refer to application instructions on bpcan.com for more information.



The Weather-Tite™ Roofing System is engineered to maximize protection in rough weather. To ensure optimum effectiveness, a roof must be installed according to BP's application instructions and respect the 5 KEY STEPS OF THE WEATHER-TITE ROOFING SYSTEM:



BP's COMPLETE WEATHER-TITE™ ROOFING SYSTEM

1

BP EAVE PROTECTORS

Considerable damage to the eaves can be caused by ice that builds up during the winter freeze/thaw cycles. **WeatherTex®** or **Gripgard** waterproofing membrane will provide the protection you need.




WEATHERTEX®



2

BP UNDERLAYMENTS


High-performance **Suredeck**, **BP lined asphalt felts**, or **BP Deckgard** provide top notch secondary protection from water driven under the shingles by high winds.



3

BP STARTER STRIP SHINGLES

Cost-effective **BP Starter Strip shingles** or **cut-off classic 3-tab shingles** reduce installation time and waste by eliminating shingle scraps, and also provide excellent protection against wind and water infiltration.



classic 3 tab shingle



premium architectural shingle

4

BP SHINGLES

BP premium architectural shingles ensure maximum protection and feature our Weather-Tite™ technology with two bands of high-tack adhesive and come in a rich palette of designer colours. Our **classic 3-tab shingles** deliver proven performance, long-term durability, and a wide selection of colours.



5

BP HIP & RIDGE

Cut-off **BP Accu-Ridge** or **classic 3-tab shingles** cap your roof with peak protection while adding an attractive finished look.



Install BP products, manufactured for quality and compatibility, to get the best return on your investment as well as long-lasting peace of mind.

Weather-Tite™ ROOFING SYSTEM WARRANTY

Exclusive to BP!

BP WEATHER-TITE™ ROOFING SYSTEM WARRANTY

RESIDENTIAL ROOFING BUILDING¹ LAMINATED SHINGLES (Manoir, Vangard 42 IR, Mystique 42) & 3-TAB SHINGLES (Yukon SB)

	CLASSIC 3-TAB SHINGLES		LAMINATED SHINGLES	
	STANDARD LIMITED WARRANTY	WEATHER-TITE™ ROOFING SYSTEM LIMITED WARRANTY	STANDARD LIMITED WARRANTY	WEATHER-TITE™ ROOFING SYSTEM LIMITED WARRANTY
WARRANTY TERM	30 YEARS		LIMITED LIFETIME	
UNIQUE to BP TOTAL PROTECTION PERIOD	UNAVAILABLE	YEAR 1 Replacement of all components of the defective area of the roof without exclusions	UNAVAILABLE	YEARS 1 AND 2 Replacement of all components of the defective area of the roof without exclusions
UP-FRONT PROTECTION PERIOD	YEARS 1 TO 5 Defective shingles and labour to install shingles only	YEARS 2 TO 10 Replacement of all components of the defective area of the roof excluding disposal	YEARS 1 TO 15 Defective shingles and labour to install shingles only	YEARS 3 TO 20 Replacement of all components of the defective area of the roof excluding disposal.
LIFETIME WARRANTY PROTECTION PERIOD	UNAVAILABLE	AFTER YEAR 10 Prorated coverage of defective shingles only	AFTER YEAR 15 Prorated coverage of defective shingles only	AFTER YEAR 20 Prorated coverage of defective shingles only
TRANSFERABILITY	1 TIME 100% - transfer within FIRST 5 YEARS Written Notification within 30 days Transfer Cost: \$100 [†]	1 TIME 100% - transfer within FIRST 10 YEARS Written Notification WITHIN 60 DAYS Transfer Cost: FREE	1 TIME 100% - transfer within FIRST 10 YEARS Written Notification within 30 days Transfer Cost: \$100 [†]	1 TIME 100% - transfer within FIRST 20 YEARS Written Notification WITHIN 60 DAYS Transfer Cost: FREE
WIND WARRANTY	REGULAR INSTALLATION 115 KM/H – 70 MPH HIGH WIND INSTALLATION 130 KM/H – 80 MPH		REGULAR INSTALLATION 180 KM/H – 110 MPH HIGH WIND INSTALLATION 220 KM/H – 135 MPH	
ALGAE WARRANTY	5 YEARS		10 YEARS	

Eligible Buildings: Single-family home (or row house with a physically delimited roof) provided the individual is the sole owner of the home that serves as the owner's residence.

DISCLAIMERS:

¹ For **NON RESIDENTIAL ROOFING** building, please refer to our website at bpcan.com.

[†] Amounts expressed in the region's corresponding currency.

Please visit bpcan.com to review all legal documents and requirements for the Standard Warranty (Standard Limited Warranty) and Weather-Tite™ Roofing System Limited Warranty.